

# TIME DOWN-HOLD ON ZERO



## FEATURES/OPERATION

- ✓ TIME DOWN HH:MM OR MM:SS
- ✓ INTERNAL DIP SWITCH PRESET
- ✓ RUN, RESET LOGIC
- ✓ 24VDC / 120VAC LOGIC
- ✓ MECHANICAL RELAY OUTPUT ON ZERO
- ✓ 2.3/4.0 INCH DIGIT - 100-200 FOOT VIEW

## LED HEIGHT/DIGITS

## PART #

2.3 INCH	4 DIGIT HH:MM/MM:SS	AF-2620-905
4.0 INCH	4 DIGIT HH:MM/MM:SS	AF-2640-905

## 2.3" DIGIT SPECIFICATIONS

LED:	2.3 Inch, 4 Digit, RED, Solid Seven Seg.
Housing:	NEMA12 Industrial Gray Painted Steel
Dimensions:	14.25" wide by 7.125" tall by 3.25" deep
Connection:	Internal Screw Terminal
Operation:	Time Down
Logic Inputs:	24VDC / 120VAC (no 24V supply)
Power:	120VAC @ less than 1 amp
Relay Contact:	N.O. / N.C. 120VAC
Output Length:	Continuous on zero

## 4.0" DIGIT SPECIFICATIONS

LED:	4.0 Inch, 4 Digit, RED, Solid Seven Seg.
Housing:	NEMA12 Industrial Gray Painted Steel
Dimensions:	22.25" wide by 10.75" tall by 3" deep
Connection:	Internal Screw Terminal
Operation:	Time Down
Logic Inputs:	24VDC / 120VAC (no 24V supply)
Power:	120VAC @ less than 1 amp
Relay Contact:	N.O. / N.C. 120VAC
Output Length:	Continuous on zero

## RELAY SPECIFICATIONS

Contact Rating	Inductive Load	Resistive Load
@ 3A 120VAC	10,000 operations	100,000 operations
@ 1A 120VAC	100,000 operations	1,000,000 operations
@ 1/2A 120VAC	1,000,000 operations	10,000,000 operations

Relay is soldered into circuit board-6 pin which is not user changeable.

## 2.3 INCH DIGIT HEIGHT



## 4.0 INCH DIGIT HEIGHT



Time down timer allows user to time down desired cycle time to aid operator in meeting company goals. Relay output available for user to wire to a light or horn for audible output on zero to inform operator that a cycle should have been completed. Hold on zero and relay output is continuous until unit is reset by activation of the preset input.

Specify 99:59 hours : minutes or minutes : seconds at time of order. 120 VAC inputs. Power is 120 VAC at 1 amp.

Preset is an internal dip switch setting and requires user to preset prior to installation. If preset changes often, please request pricing on our metronome series.

NEMA12 models offer internal screw terminal connection for customer to punch holes in 16 gauge steel housing and run conduit/wire into the cabinet to strip and screw terminate. Models do not come with any knockouts or power cords.

**Phone: 614-851-1100**

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228  
Phone: 614-851-1100 Fax: 614-851-1121

[www.ledgible.com](http://www.ledgible.com)  
[www.ledandon.com](http://www.ledandon.com)