

# 2.3" 6 DIGIT COUNTER



## BUILT TO ORDER:

Built to order items are non-stocked items and are fabricated on an order by order basis as needed. Please review user manual and specifications in detail before ordering as these units are non-returnable / non-refundable and require written acceptance of these terms.

## USER MANUAL:

<http://www.ledgible.com/manuals/PB-2149-321B.pdf>

## INDOOR LED DESCRIPTION:

Numeric 2.3 inch digit height up to 6 digit width with decimal control. RED solid seven segment LED rated 100,000 Hr lifespan. Single sided viewing.

## POWER DRAW DESCRIPTION:

120VAC @ less than 1 amp.

## N1 ENCLOSURE DESCRIPTION:

The enclosure is NEMA 1 black painted steel, 14.25" wide by 6.75" tall by 3.5" deep. The marquee is designed to be hung using the eyelets on the top of the unit, or bolted to a wall using the wall mount tabs.

## CABLE/CONNECTION:

An industry standard five foot three prong 120VAC power cord is provided with the unit. Unit includes A DB9 male connector. No cable provided.

## OPERATION DESCRIPTION:

RS-232, RS-422, or RS-485 communications at all standard baud rates from 150 baud to 19200 baud. Each Trimline Marquee has an address set via dip switch allowing a single control system to send data to up to 64 marquees in a single multi-drop communications network.

## FEATURES/OPERATION

- ✓ CNT UP, RESET INPUTS
- ✓ 24VDC / 120VAC LOGIC
- ✓ 2.3 INCH DIGIT - 115 FOOT VIEW
- ✓ MEMORY BACKUP DURING POWER LOSS
- ✓ LIGHT INDUSTRIAL HOUSED
- ✓ INDOOR BRIGHT RED L.E.D.

## DESCRIPTION

## PART #



LED DISPLAY	TL-2425-116
MANUAL BUTTON COUNT	KT-2764-058
PHOTO EYE KIT, 15' CABLE	KT-2764-026

## SPECIFICATIONS

LED:	2.3 Inch, 6 Digit, Solid Seven Seg.
LED Life:	100,000 Hours (11.4 years)
LED Color:	RED
AC Cord:	Industry Standard 3 Prong 5' Power Cord
Power:	120VAC @ less than 1 amp
Dimensions:	14.25" wide by 6.75" tall by 3.5" deep
Housing:	NEMA 1, Black Painted Steel
Temperature:	0 F to 122 F (-17C to +50C)
Viewing:	Up to 115 Feet, Single Sided View
Max. Count:	999999
Logic Inputs:	Count Up, Reset
Input Accept:	24VDC current sourcing (PNP) outputs or 120VAC outputs
Max. Rate:	10Hz @ 50% Duty Cycle
Manual #:	PB-2149-321

## OPTIONAL ACCESSORIES

### SPECIFICATIONS-OPTIONAL ACCESSORIES

	The KT-2764-058 is an installation kit which contains a manual count up push button and reset push button. NEMA 12/4 ABS. 15 feet of cable prewired with 120VAC power cord.
	KT-2764-026 installation kit containing a retro-reflective photo with reflector and enclosure with a reset pushbutton. 15ft cable included.

**Phone: 614-851-1100**

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228

Phone: 614-851-1100 Fax: 614-851-1121

[www.ledgible.com](http://www.ledgible.com)

[www.ledandon.com](http://www.ledandon.com)