

4.0" 6 DIGIT TIMER



BUILT TO ORDER:

Built to order items are non-stocked items and are fabricated on an order by order basis as needed. Please review user manual and specifications in detail before ordering as these units are non-returnable / non-refundable and require written acceptance of these terms.

USER MANUAL:

<http://www.ledgible.com/manuals/PB-2149-322.pdf>

INDOOR LED DESCRIPTION:

Numeric 4.0 inch digit height up to 6 digit width. Format HH:MM:SS up to 99:59:59. RED solid seven segment LED rated 100,000 Hr life span. Single sided viewing.

POWER DRAW DESCRIPTION:

120VAC @ less than 1 amp.

N1 ENCLOSURE DESCRIPTION:

The enclosure is NEMA 1 black painted steel housing, 24" wide by 6.75" tall by 3.125" deep. The marquee is designed to be hung using the eyelets on the top of the unit, or bolted to a wall using the wall mount tabs.

CABLE/CONNECTION:

An industry standard five foot three prong 120VAC power cord is provided with the unit. Unit includes mating micro-change connector with 6 foot cable for customer termination.

OPERATION DESCRIPTION:

Time up. Standard input logic is time up (maintained), reset (momentary). Trimline inputs are compatible with 24VDC current sourcing (PNP) outputs or 120VAC outputs. NO PRESET time down capability.

MEMORY:

Unit provides last value memory backup during power loss for up to one week without power.

FEATURES/OPERATION

- ✓ RUN UP, RESET INPUTS
- ✓ 24VDC / 120VAC LOGIC
- ✓ 4.0 INCH DIGIT - 200 FOOT VIEW
- ✓ MEMORY BACKUP DURING POWER LOSS
- ✓ LIGHT INDUSTRIAL HOUSED
- ✓ INDOOR BRIGHT RED L.E.D.

DESCRIPTION

PART

LED DISPLAY	TL-2451-116
MANUAL BUTTON COUNT	KT-2764-062

SPECIFICATIONS

LED:	4.0 Inch, 6 Digit, Solid Seven Seg.
LED Life:	100,000 Hours (11.4 years)
LED Color:	RED
AC Cord:	Industry Standard 3 Prong 5' Power Cord
Power:	120VAC @ less than 1 amp
Dimensions:	24.00" wide by 6.75" tall by 3.125" deep
Housing:	NEMA 1, Black Painted Steel
Temperature:	0 F to 122 F (-17C to +50C)
Viewing:	Up to 200 Feet, Single Sided View
Max. Count:	99:59:59
Logic Inputs:	Time Up, Reset
Input Accept:	24VDC current sourcing (PNP) outputs or 120VAC outputs
Max. Rate:	10Hz @ 50% Duty Cycle
Manual #:	PB-2149-322

OPTIONAL ACCESSORIES

SPECIFICATIONS-OPTIONAL ACCESSORIES



The KT-2764-062 is an installation kit which contains a manual RUN selector switch and RESET push button. NEMA 12/4 ABS. 15 feet of cable prewired with 120VAC power cord.

Phone: 614-851-1100

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228

Phone: 614-851-1100 Fax: 614-851-1121

www.ledgible.com

www.ledandon.com