

LED SERIAL SLAVE

RS232/422/485 ASCII COMMAND



FEATURES/OPERATION

- ✓ RS232/422/485 SIMPLE ASCII PROTOCOL
- ✓ 120VAC POWER
- ✓ 8.0 INCH DIGIT - 400 FOOT VIEW
- ✓ MEMORY BACKUP VALUE DURING POWER LOSS
- ✓ INDUSTRIAL HOUSED N12
- ✓ INDOOR BRIGHT RED L.E.D.

POWER DRAW DESCRIPTION
The marquee requires 120VAC power at 60Hz (50Hz acceptable). The units power draw is 120VAC @ less than 1 amp.

N12 ENCLOSURE DESCRIPTION:
The enclosure is NEMA 12 painted steel with dust gasket. The marquee is designed to be hung using the eye bolts on the top of the unit, or may optionally be bolted to a wall using separately purchased wall mount brackets. No power or data cabling provided.

NEMA12 INSTALL DISCLAIMER:
Electrical terminations are provided within the enclosure requiring the customer to punch holes in the 14 gauge steel housing and run conduit/wire into the enclosure. Electrical terminations within the enclosure are screw terminals.

OPERATION DESCRIPTION:
RS-232, RS-422, or RS-485 communications at all standard baud rates from 150 baud to 19200 baud. Each Trimline Marquee has an address set via dip switch allowing a single control system to send data to up to 64 marquees in a single multi-drop communications network.

Size/Housing Selection Chart (Indoor Red)

DESCRIPTION	PART #
8.0" 4 Digit RS232/422/485, NEMA12, 1 Sided	TL-2481-314
8.0" 6 Digit RS232/422/485, NEMA12, 1 Sided	TL-2481-316

DIMENSIONS
4 Digit Counter Housing: 30" wide by 16.75" tall by 5" deep
6 Digit Counter Housing: 43.75" wide by 18" tall by 5" deep

MANUAL # PB-2149-320

BUILT TO ORDER: Built to order items are non-stocked items and are fabricated on an order by order basis as needed. Please review user manual and specifications in detail before ordering as these units are non-returnable / non-refundable and require written acceptance of these terms.

USER MANUAL: :
<http://www.ledgible.com/manuals/PB-2149-320C.pdf>

INDOOR LED DESCRIPTION:
Numeric 8.0 inch digit height up to 4 digit width. RED discrete seven segment LED rated 100,000 Hr life span. Single sided viewing.

Phone: 614-851-1100
American LED-gible Inc.
1776 Lone Eagle Street Columbus, Ohio 43228
Phone: 614-851-1100 Fax: 614-851-1121
www.ledgible.com
www.ledandon.com