



LED ANNUNCIATOR



**Red/Yellow/Green
L.E.D.**

This rectangular tri-color LED indicator is a low price solution for viewing of alarm states, status indication, run/down states and more. Window is 2.72 inch wide by 0.95 inch tall for viewing up to 130 feet. Compact, panel mount design is great for OEMs.

SPECIFICATIONS

Viewing Window: 24.2mm x 69mm (0.95" x 2.72")
Overall Length: 84.6mm (3.33")
Overall Width: 38.6mm (1.52")
Overall Depth: 76.5mm (3.01")
Req'd Panel Cutout: 32mm x 78mm (1.26" x 3.07")
Req'd Panel Depth: 73mm (2.88")
Rating: CE, CCC, CCS conformity & safety

Wiring is common screw terminal interface. With X2 as -Ground Common, to actuate Red, simply connect X1 with +24 VDC/120VAC. To actuate Green, connect X3 with +24VDC/120VAC. To actuate Yellow, connect X1 and X3 to +24VDC/120VAC. Power consumption is 0.8 Watts.


VOLTAGE COLOR

VOLTAGE	COLOR	PART #
24VDC	R/Y/G	LD-2837-820
120VAC	R/Y/G	LD-2837-810

LED BEACONS

LD-2648-700

LD-2648-701



**52mm
Red/Yellow/Green
L.E.D.**

The LD-2648-700 offers 360 degree viewing angle, as well as, viewable from above (top view). This beacon is versatile in industrial and non-industrial environments.

SPECIFICATIONS

Diameter: 52mm (2")
LED: RED/YELLOW/GREEN
Voltage: 24VDC


These LED light beacons can be actuated to illuminate Red, Amber, or Green internal LEDs. With a 360 degree viewing angle, these beacons are a versatile product in industrial and non-industrial environments alike.

These lights are versatile in mounting and can be machine, ceiling, pole, control panel or surface mounted.

The lights are 2 inch in diameter and easy to install. Mounting can be performed via 2 threaded inserts (thread type M4x0.7) or adherence tapes (suggested versions are 3M VHB Tapes). Mounting hardware is not provided by LEDAndon.com.

VOLTAGE COLOR

VOLTAGE	COLOR	PART #
24VDC	R/Y/G w/top view	LD-2648-700
24VDC	R/Y/G no top view	LD-2648-701



Phone: 614-851-1100

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228

Phone: 614-851-1100 Fax: 614-851-1121

www.ledgible.com

www.ledandon.com